

SLPM Series Magnetic Pulse Solenoid Valve

●The Professional Solenoid Valves Manufactory

Characteristics

This series valve is famous for sensitive reaction and high pressure.

Usually be used to circuit control board connection, it's good for energy saving.

Widely used to IC card gas combustion meter, water saving irrigation, water meter and various automatism sanitation.

The core of the valve can be pulled and stretched to be the good shape, with good strictness, credibility, sensitive reaction and long life-spen.

Using Condition

Fluid Media: Water, Gas(but not corrosive)
Fluids Temp.: ≤60℃, Pls use at the area which relative Temp. can not over then 85%

How to Use

To exchange the poles of the battery for on-off



Technical Parameter

Model Code	SLPM-10	SLPM-15	SLPM-20	SLPM-25	SLPM-35	SLPM-40	SLPM-50
Length(A)	66.5	66.5	75	96	131	131	165
Width(B)	48	48	58	70	96	96	120
Height(C)	82.5	82.5	88	101	116	116	142
Pipe Size	3/8"	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"

Note: Pls contact the factory for detailed parameter

Specifications

Pipe Size	3/8"	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"
Operating Mode	Pilot Operated						
Orifice	13mm	13mm	20mm	25mm	35mm	40mm	50mm
Sea Keeping Pressure	0.5 ~ 10kgf/cm ²						
Diaphragm Material	Standard: NBR Options: VITON, EPDM						
Available Voltage	Pulse 6 ~ 24V DC (Contact the factory for others)						
pulse	50 ~ 80ms						
Body Material	Forged Brass						

Construction, External Dimensions Char

